

DATA SHEET

EPURTEX

PRODUCT DESCRIPTION: Nonwoven needled textile

FUNCTION: Separation

RAW MATERIAL: Polypropylene

TECHNICAL DATA TABLE

	PROPERTIES	TEST METHOD	VALUES	
			Metric	Imperial
PHYSICAL	Thickness	ASTM D5199	0,6 mm	24 mils
	Mass per unit area	ASTM D5261	$75 \text{ g/m}^2 \pm 15 \%$	$2,2 \text{ oz/yd}^2 \pm 15 \%$
MECHANICAL	Tensile strength	CAN/CGSB-148.1 - No 7.3	180 N	40 lb
	Elongation at break	CAN/CGSB-148.1 - No 7.3	55 - 95 %	
	Tear strength	CAN/CGSB-4.2 - No 12.2	65 N	15 lb
HYDRAULIC	Permittivity	CAN/CGSB-148.1 - No 4	6,0 s ⁻¹	
	Filtration opening size (FOS)	CAN/CGSB-148.1 - No 10	180 μm	
DIMENSIONS	Standard size	-	1,5 m X 50 m	4,9 ft X 164 ft
			1,5 m X 150m	4,9 ft X 492 ft
			3 m X 150 m	9,8 ft X 492 ft

The information contained herein is provided at no cost or obligation on the part of Soleno Textile Inc. The individual using this information in their possession assumes full responsibility for its use, including that of ensuring that this technical data sheet is the latest update by contacting Soleno Textile Inc. Values are calculated using the minimum average roll value (MARV), as defined by ASTM D-4439. Roll sizes can vary 0.5% from standard sizes

Soleno Textile Inc. offers no guarantee regarding the use, installation or fitness for purpose of its geotextiles described in this document. Since conditions of use and handling of our products can vary and are beyond the control of Soleno Textile Inc., it can in no way be held responsible for the product's performance and the consequences of improper installation or use. Soleno Textile Inc.must be advised of any defect or non-compliance of its product before installation. Soleno Textile Inc.'s liability is limited to the replacement of the defective or noncompliant product, with the exception of any legal or contractual warranty.

APPLICATION: Septic fields