

# **SPECIFICATIONS**

### CORRUGATED MANHOLE/CATCH BASIN

#### SCOPE

These specifications apply to all 300 mm (12 in) to 1 200 mm (48 in) diameter corrugated manholes/catch basins used for collecting non-roadway surface runoff.

### MANHOLE REQUIREMENTS

The manhole/catch basin shall be made with smooth interior and corrugated exterior walls and manufactured from a single part.

#### PRODUCT COMPONENTS

The manhole/catch basin components shall be made from high-density polyethylene (HDPE) resin that complies with standard ASTM D3350.

#### JOINT PERFORMANCE

- 100 mm (4 in) to 250 mm (10 in): double bell with integrated gasket (DBIG). The DBIG and Solflo Max assembly is certified as per standard CSA B182.8, Type 1. The gasket shall be co-injected into the bell and shall overlap two corrugations.
- 300 mm (12 in) to 900 mm (36 in): bell with integrated gasket with clips (BIGC). The BIGC and Solflo Max assembly is certified as per standard CSA B182.8, Type 1. The gasket shall be co-injected into the bell and shall overlap two corrugations.
- 1050 mm (42 in): bell with gasket (BG) installed by the manufacturer onto the male end, covered by a protective film for shipping. The
  assembly is certified as per standard CSA B182.8, type 3.
- 1200 mm (48 in): bell with integrated gasket with clips (BIGC). The BIGC and Solflo Max assembly shall comply with standard CSA B182.8.
- Gaskets shall comply with table 3 from standard BNQ 3624-120 and table 6 from standard CSA B181.0.

#### **GRATES AND COVERS**

Frames, grates, and covers shall be made from S series cast iron.

### **ACCESSORIES**

- Ladder made of galvanized steel.
- Ladder made of other materials (upon request).
- Anchors made of stainless steel.

## **DIMENSIONS AND QUANTITIES**

Dimensions and quantities shall comply with tender documents and drawings.

## TNSTALL ATTON

Installation shall be carried according to the installation requirements of the concrete manhole/catch basin specified in standard BNQ 1809-300, and following Soleno's recommendations. Contact the Soleno representative in your region or visit our website at soleno.com for installation recommendations.